

Full HD Laser Projector

Highlights

- Advanced laser & LED hybrid light sources for brilliant color rendition
- Full HD resolution for 1080p multimedia contents
- 20,000 hour life span to save on total cost of ownership
- 2 sets of HDMI, composite, and S-video versatile inputs
- Integrated 2W*2 speaker for multimedia applications



Specifications

Display	Chipset	TI DMD 0.65	
	Resolution	1920 (H) x 1080 (V)	
	Lens	1.2X	
	Keystone Correction	+30 ~ -30	
	Projection Size	38" ~ 150" (Diagonal)	
	Throw Distance	1.5M ~ 5M	
	Throw Ratio	1.5 ~ 1.8	
	Lamp	Nichia Blue laser NDB7775+ Luminus PT54 R/B LED	
	Lamp Life (Normal / Eco)	>20,000 Hours	
	Brightness	1,600 lm	
Audio	Speaker	2W *2	
	Input Signal	Computer and Image	NTSC M (3.58 MHz), 4.43MHz PAL (B, D, G, H, I, M, N, 60) SECAM (B, D, G, K, K1, L) 480i and 576i 480p and 576p 720p, 1080i, 1080p
		Frequency	Horizontal: 15 ~ 100 kHz Vertical: 50 ~ 85 Hz
		Compatibility	PC 1920 x 1080 @ 60Hz (Native)
		MAC Analog	1152 x 870 @ 75Hz (*May Require MAC Adaptor)

Connectivity	RGB Input	DB-15 *1
	HDMI Input	HDMI *2
	Component Input	Share with RGB *1
	S-Video Input	*1
	Composite Input	*1
	Audio In	3.5mm Mini-stereo Jack *1
Power	Audio Out	3.5mm Mini-stereo Jack *1
	RS232	DB-9 *1
	Voltage	100V ~ 240Vac 50 / 60Hz
Language	Consumption	>192W (Max.)
	Operating Environment	English / Dutch / French / Spanish / Italian / Korean / Thai / Portuguese / T. Chinese / S. Chinese / Japanese / Russian / German / Swedish / Turkish / Finnish / Polish
Operating Environment	Temperature	0° ~ 40° C / 32° ~ 104° F
	Humidity	10 ~ 90% (Non- condensation)
	Altitude	0 ~ 6,000 Feet
Dimension	Physical (mm)	321 x 247.5 x 110.5
	(W x D x H) (inch)	12.64" x 9.74" x 4.35"
Weight	Net	8.8lbs / 4kg
Regulations		RoHS, CB, CCC, PSB, C-tick, KC, SASO, CE, GOST-R, Ukr, ErP, SVHC, list & REACH DoC, UL, FCC (including ICES-003), cUL / CSA, Argen, NOM

*Specifications are subject to change without notice.